


### SOLAR AREA LIGHT





- 50W hybrid area light switches from cost-free solar to line voltage, only when the long-lasting battery is depleted.
- All-in-one design.
- Exclusive long-lasting battery withstands extreme temperatures.
- Easy to install and operate.
- Adjustable solar panel can be mounted up to 16 ft away from light engine.
- Custom optics and color temperatures available.
- Advanced battery lasts at least 2,000 charge cycles.
- See pg. 2 for product dimensions & accessories.
- See pg. 3 for photometrics.

LAR ARRAN	UN 38.3	6-10 HRS	-4°F TO 149°F	UP TO 50 HRS			-4°F TO 149°F	L70
	CERTIFIED BATTERY C	BATTERY HARGE TIME C	BATTERY CHARGE TEMP	BATTERY LIFE	REPLACEABLE BATTERY	MOTION SENSING	OPERATING TEMP	100,000hrs RATED LIFE
	PART #	UPC	COMPARES TO	LUMENS	COLOR	EPA	LISTINGS	
SL-SAL-H	YB-50W-40K-SF-BK-G2	844006081430	400W	9800	4000K	6.1		

OPERATING MODES | 🕒 TIMER | 🛠 MOTION SENSING

BRACKET & ADDITIONAL SOLAR PANEL - MUST ORDER SL-SAL-50W-2PANELKIT SEPARATELY (SHIPPED IN A SEPARATE BOX)

PART #	DESCRIPTION				
SL-SAL-50W-2PANELKIT	2X 50W SOLAR PANELS, 10 FOOT EXTENSION CABLE, 6 FOOT Y-CABLE, ADJUSTABLE BRACKET				

FOR POLE MOUNTING 4 U-BOLTS ARE REQUIRED SEE PG.2 FOR MORE DETAILS.

(U-BOLTS NOT INCLUDED)

FOR LISTING STATUS GO TO LED-LLC.COM

EASY TO + INSTALL

## **Light Efficient Design**

847.380.3540 • led-llc.com • sales@led-llc.com








**TECHNICAL INFORMATION** 


# 


#### DIMENSIONS











#### ACCESSORIES

	BRACKETS	OPTIONAL MOUNTING HARDWARE (NOT INCLUDED)			
PART #	DESCRIPTION	PART #	DESCRIPTION	QTY REQ.	
SL-SAL-BKT-RP-BK-G1	ROUND POLE BRACKET	SL-UBOLT-4IN-ROUND	FITS 4" ROUND POLE		
SL-SAL-BKT-SP-BK-G1	SQUARE POLE BRACKET	SL-UBOLT-4IN-SQUARE	FITS 4"SQUARE POLE		
SL-SAL-BKT-ST-3-BK-G1	TENON ADAPTER FOR 3" SQUARE POLE	SL-UBOLT-5IN-ROUND	FITS 5" ROUND POLE	4 U-BOLTS	
SL-SAL-BKT-RT-3-BK-G1	TENON ADAPTER FOR 3" ROUND POLE	SL-UBOLT-5IN-SQUARE	FITS 5"SQUARE POLE		
SL-SAL-BKT-WM-BK-G1	WALL MOUNT BRACKET				

STANDARD SLIP FITTER MOUNTING BRACKET INCLUDED.

CONTACT US FOR ADDITIONAL BRACKET OPTIONS.

FOR USE W/ SL-SAL OFF-GRID + HYBRID MODELS









SQ TENON





WALL MOUNT

## **Light Efficient Design**

847.380.3540 • led-llc.com • sales@led-llc.com






## **TECHNICAL INFORMATION**




#### **PHOTOMETRICS**

FOOT CANDLES	ISO-LINE COLOR		
1 FC	BLACK		
0.5 FC	MAGENTA		
0.1 FC	BLUE		



#### **MOUNTING HEIGHT : 25FT**

**MOUNTING HEIGHT : 30FT** 



## **Light Efficient Design**

847.380.3540 • led-llc.com • sales@led-llc.com

