

FREE TO SHINE



HYBRID LED SOLAR AREA LIGHT COMPARES TO 400W HID

- 50W hybrid area light switches from cost-free solar, to line voltage, only when the long-lasting battery is depleted
- New MPPT Solar Charge Controller optimizes charging under all conditions.
- All-in-one design
- Exclusive long-lasting battery withstands extreme temperatures
- Easy to install and operate
- Adjustable solar panel can be mounted up to 16 ft away from light engine
- Custom optics and color temperatures available
- LED Operating Temperature Range = -40F to 140F Battery Operating Temperature = -4F to 140F

C	E	F©
(E	FC

PART #	UPC	COMPARABLE TO	LUMENS	сст	EPA
SL-SAL-HYB-50W-40K-SF-BK-G2	844006081430	400W	9800	4000K	6.1

BRACKET & ADDITIONAL SOLAR PANEL (MUST ORDER SL-SAL-50W-2PANELKIT - SHIPS IN SEPARATE BOX)

		DESCRIPTION						
SL-SAL-50W-2PANELKIT		2X 50W SC	DLAR PANELS, 1	0 FOOT EXTE	NSION CABLE, &	FOOT Y-CABLE	, ADJUSTABLE	BRACKET
1st to market	UP TO 50 HRS BATTERY LIFE	-40°F to 140°F	-4°F to 140°F	TRAVEL CERTIFIED BATTERY SAFETY	REPLACEABLE BATTERY	MOTION SENSOR	L70 >100,000 RATED LIFE	LIMITED WARRANTY

solera-solar.com • 847.38

847.380.3540

LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013 INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949 847.380.3540 • led-llc.com




05.24.23 Information is subject to change without notice.




FREE TO SHINE

Fixture Side View




Fixture Top View



(Total fixture weight = 30lbs)

YBRID



ADDITIONAL BRACKETS MUST BE PURCHASED SEPARATELY (SLIP-FITTER BRACKET INCLUDED WITH FIXTURE)

ADDITIONAL BRACKETS & ACCESSORIES	SOLERA PART # SL-SAL-BKT-RP-BK-G1 SL-SAL-BKT-SP-BK-G1 SL-SAL-BKT-ST-3-BK-G1 SL-SAL-BKT-RT-3-BK-G1	DESCRIPTION Round pole bracket Square pole bracket 3" square tenon bracket 3" round tenon bracket	
Ċ	SL-SAL-BKT-WM-BK-G1	Wall mount bracket	

SL-SAL-BKT-RP-BK-G1

SL-SAL-BKT-SP-BK-G1

SL-SAL-BKT-ST-3-BK-G1





SL-SAL-BKT-WM-BK-G1

Default Setting - No Adjustments Necessary

The default setting is Dusk 'till Dawn @ 80% first 2 hours, 50% constant & 80% w/ motion for the rest of the night.

LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013 INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949 847.380.3540 • led-llc.com

