

FREE TO SHINE



OFF-GRID LED SOLAR AREA LIGHT COMPARES TO 400W HID

- Off-Grid completely free to operate, plus no trenching or wiring required
- All-in-one design
- Exclusive long-lasting battery withstands extreme temperatures
- Easy to install and operate
- Adjustable solar panel can be mounted up to 16 ft away from light engine
- Custom optics and color temperatures available

CE FC

| PART # | UPC | COMPARABLE TO | LUMENS | сст | EPA |
|----------------------------|--------------|---------------|--------|-------|-----|
| SL-SAL-OG-50W-50K-SF-BK-G1 | 844006050405 | 400W | 9800 | 5000K | 6.1 |


BRACKET & ADDITIONAL SOLAR PANEL - MUST ORDER SL-SAL-50W-2PANELKIT SEPARATELY (SHIPPED IN A SEPARATE BOX)

| PART # | DESCRIPTION | | | | | |
|----------------------|--|--|--|--|--|--|
| SL-SAL-50W-2PANELKIT | 2X 50W SOLAR PANELS, 10 FOOT EXTENSION CABLE, 6 FOOT Y-CABLE, ADJUSTABLE BRACKET | | | | | |
| | | | | | | |



847.380.3540 • led-llc.com









•

REPLACEABLE BATTERY









solera-solar.com

847.380.3540

LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013 INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949




03.23.23 Information is subject to change without notice.




FREE TO SHINE

Fixture Side View




Fixture Top View



(Total fixture weight = 30lbs)

OFF-GRID LED SOLAR AREA LIGHT COMPARES TO 400W HID



ADDITIONAL BRACKETS MUST BE PURCHASED SEPARATELY (SLIP-FITTER BRACKET INCLUDED WITH FIXTURE)

| ETS | SOLERA PART # | DESCRIPTION | DESCRIPTION | | |
|-----------------------------------|-----------------------|--------------|-------------------------|--|--|
| DITIONAL BRACKET & ACCESSORIES | SL-SAL-BKT-RP-BK-G1 | Round pole | bracket | | |
| | SL-SAL-BKT-SP-BK-G1 | Square pole | bracket | | |
| CCES | SL-SAL-BKT-ST-3-BK-G1 | 3" square te | 3" square tenon bracket | | |
| & AC | SL-SAL-BKT-RT-3-BK-G1 | 3" round te | 3" round tenon bracket | | |
| ADD | SL-SAL-BKT-WM-BK-G1 | Wall mount | bracket | | |
| | | - | | | |





SL-SAL-BKT-ST-3-BK-G1

SL-SAL-BKT-RT-3-BK-G1

SL-SAL-BKT-WM-BK-G1

• Default Setting - No Adjustments Necessary

The default setting is Dusk 'till Dawn @ 80% first 2 hours, 50% constant & 80% w/ motion for the rest of the night.

LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013 INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949 847.380.3540 • led-llc.com

