

FREE TO SHINE



HYBRID LED SOLAR AREA LIGHT COMPARES TO 400W HID

- 50W hybrid area light switches from cost-free solar, to line voltage, only when the long-lasting battery is depleted
- All-in-one design
- Exclusive long-lasting battery withstands extreme temperatures
- Easy to install and operate
- Adjustable solar panel can be mounted up to 16 ft away from light engine
- Custom optics and color temperatures available
- Operating Temperature Range = -4F to 140F

CE F©

| PART # | UPC | COMPARABLE TO | LUMENS | сст | EPA |
|-----------------------------|--------------|---------------|--------|-------|-----|
| SL-SAL-HYB-50W-40K-SF-BK-G1 | 844006074418 | 400W | 9800 | 4000K | 6.1 |

BRACKET & ADDITIONAL SOLAR PANEL (INCLUDED WITH PURCHASE - SHIPPED IN A SEPERATE BOX)

| PART # | DESCRIPTION | | | | | |
|----------------------|---|---|------------------------|---------------|------------|---------------------|
| SL-SAL-50W-2PANELKIT | 2X 50W SOLAR PANELS, 10 FOOT EXTENSION CABLE, 6 FOOT Y-CABLE, ADJUSTABLE BRACKET | | | | | |
| ISU to market | LP TO 50 IRS TERY LIFE OPERATING TEMP | UN 38.3 O TRAVEL CERTIFIED BATTERY SAFETY | REPLACEABLE BATTERY | MOTION SENSOR | FATED LIFE | LIMITED WARRANTY |
| | solera-sola | n.com • 84 | 17.380.35 4 | 40 | | |


LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013 INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949 847.380.3540 • led-llc.com






FREE TO SHINE

Fixture Side View




Fixture Top View



(Total fixture weight = 30lbs)

HYBRID



ADDITIONAL BRACKETS MUST BE PURCHASED SEPARATELY (SLIP-FITTER BRACKET INCLUDED WITH FIXTURE)

| ETS | SOLERA PART # | DESCRIPTION | | | | | | |
|------------------------------------|-----------------------|-------------------------|-------------------------|--|--|--|--|--|
| DITIONAL BRACKETS & ACCESSORIES | SL-SAL-BKT-RP-BK-G1 | Round pole bracket | | | | | | |
| | SL-SAL-BKT-SP-BK-G1 | Square pole bracket | | | | | | |
| | SL-SAL-BKT-ST-3-BK-G1 | 3" square tenon bracket | 3" square tenon bracket | | | | | |
| & AC | SL-SAL-BKT-RT-3-BK-G1 | 3" round tenon bracket | | | | | | |
| ADC | SL-SAL-BKT-WM-BK-G1 | Wall mount bracket | | | | | | |
| | | | | | | | | |





SL-SAL-BKT-SP-BK-G1



SL-SAL-BKT-ST-3-BK-G1





SL-SAL-BKT-WM-BK-G1



The default setting is Dusk 'till Dawn @ 80% first 2 hours, 50% constant & 80% w/ motion for the rest of the night.

LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013 INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949 847.380.3540 • led-llc.com

